

OUTDOOR Enclosure Air Conditioner



Technical Specifications

Model	Bs500	Bs1000	Bs2000	Bs3000	Bs4000
Type	Wall mounted	Wall mounted	Wall mounted	Wall mounted	Wall mounted
Cooling capacity I35 I35	500 watt	1000 Watt	1700 Watt	2700 Watt	4000 Watt
Type of refrigerant	R 134	R134a	R134a	R134a	R22
Amount of refrigerant	650 g	650 g	750 g	800 g	1100 g
Rated frequency	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz	50/60 Hz
Standard power supply	198 V-252 V	198 V-252 V	198 V-252 V	198 V-252 V	198 V-252 V
Power absorbed L35 L35	690 W	690 W	890 W	1200 W	1870 W
Compressor	DANFOSS/EMBRACO	DANFOSS/EMBRACO	DANFOSS/EMBRACO	DANFOSS/EMBRACO	KULTHORN
Ambient temperature range	+15°C ...+55°C	+15°C ...+55°C	+15°C ...+55°C	+15°C ...+55°C	+15°C ...+55°C
internal circuit (m3/h)	240	490	520	810	1400
Internal fan type	Backward	Backward	Backward	Backward	Backward
External circuit (m3/h)	490	780	780	960	2030
External fan type	Axial	Axial	Axial	Axial	Axial
Control range	+30°...+45°C	+30°...+45°C	+30°...+45°C	+30°...+45°C	+30°...+45°C
Factory setting	+30°C	+30°C	+35°C	+35°C	+35°C
Colour	RAL 7047	RAL 7047	RAL 7047	RAL 7047	RAL 7047
Weight	40 kg	40 kg	55 kg	63 kg	76 kg
H×W×D (mm)	570×300×200	850×400×245	1000×410×285	1100×460×285	1400×460×350
IP	54	54	54	54	54

www.bentlyco.ir

