



| Model | Bch2000 | Bch3500 | Bch7000 | Bch17000 | Bch35000 |
|-----------------------------|------------------------|------------------------|------------------------|------------------------|----------------------------|
| Cooling capacity I35 | 1750 watt | 3500 watt | 7000 watt | 17000 watt | 35000 watt |
| Cooling capacity I35 | 1/2 TON | 1 TON | 2 TON | 5 TON | 10 TON |
| Type of refrigerant | R134a | R134a | R22 | R22 | R22 |
| Amount of refrigerant | 1000gr | 1500 gr | 2300 gr | 3000 gr | 3800 gr |
| Power consumption | 220-240 V 50H/1PH | 220-240 V 50H/1PH | 380-420 V 50H/1PH | 380-420 V 50H/1PH | 380-420 V 50H/1PH |
| Compressor | Danfoss/ Embraco | Danfoss/ Embraco | Kulthorn | Copeland | Copeland |
| Maximum working temperature | 55 | 55 | 55 | 55 | 55 |
| Fan | 1200 m ³ /h | 1500 m ³ /h | 3200 m ³ /h | 9600 m ³ /h | 6500 m ³ /h * 2 |
| Pump | Pentax 0.37 kw | Pentax 0.37 kw | Pentax 0.37 kw | Pentax 0.74 kw | Pentax 1.5 kw |
| Temperature controller | Elite | Elite | Elite | Elite | Elite |
| Control Range | +7 ... +40 | +7 ... +40 | +7 ... +40 | +7 ... +40 | +7 ... +40 |
| Pressure controller | Danfoss | Danfoss | Danfoss | Danfoss | Danfoss |
| Factory setting | +12 | +12 | +12 | +12 | +12 |
| Tank volume | 35 m ³ | 45 m ³ | 120 m ³ | 140 m ³ | 160 m ³ |
| H×W×D mm | 840×500×700 | 840×500×700 | 950*500*700 | 1200*760*910 | 1200*710*120 |

Technical Specifications

www.bentlyco.ir

